




产品目录

PRODUCT CATALOG

10G XFP

 TOPLINK	Part Number	Data Rate	Wavelength(nm)	Tx Power(dBm)	Rx Sen(dBm)	Reach	Connector	Temp.
XFP	XFP-MM85TG-S3Dx	10.3Gb/s	850	-6.5 ~ -0.5	≤-11.1	300m(SR)	Duplex LC	C/I
	XFP-SM31TG-10Dx	10.3Gb/s	1310	-6.5 ~ +0.5	≤-14.5	10km(LR)	Duplex LC	C/I
	XFP-SM31TG-20Dx	10.3Gb/s	1310	-3 ~ +2	≤-15	20km	Duplex LC	C/I
	XFP-SM55TG-40Dx	10.3Gb/s	1550	-1 ~ +2	≤-16	40km(ER)	Duplex LC	C/I
	XFP-SM55TG-80Dx	10.3Gb/s	1550	0 ~ +4	≤-23	80km(ZR)	Duplex LC	C/I
	XFP-SM55TG-A0DC	10.3Gb/s	1550	1 ~ +4	≤-25	100km	Duplex LC	C
XFP CWDM (EML)	XFP-CWxxTG-40Dx	10.3Gb/s	1470-1610	-1 ~ +2	≤-16	40km	Duplex LC	C/I
	XFP-CWxxTG-80Dx	10.3Gb/s	1470-1610	0 ~ +4	≤-23	80km	Duplex LC	C/I
XFP CWDM (DFB)	XFP-CDxxTG-10Dx	10.3Gb/s	1270-1570	-3.0 ~ +2.0	≤-14	10km	Duplex LC	C/I
	XFP-CDxxTG-20Dx	10.3Gb/s	1270-1450	-3.0 ~ +2.0	≤-15	20km	Duplex LC	C/I
	XFP-CDxxTG-40Dx	10.3Gb/s	1270-1390	0 ~ +5	≤-16	40km	Duplex LC	C/I
	XFP-CDxxTG-60Dx	10.3Gb/s	1270-1330	+1 ~ +6	≤-21	60km	Duplex LC	C/I
	XFP-CDxxTG-05Dx	10.3Gb/s	1590-1610	-3.0 ~ +2.0	≤-15	5km	Duplex LC	C/I
XFP DWDM	XFP-DWxxTG-40Dx	10.3Gb/s	ITU-T G.692 C21-61	-1 ~ +2	≤-16	40km	Duplex LC	C/I
	XFP-DWxxTG-80Dx	10.3Gb/s	ITU-T G.692 C21-61	0 ~ +4	≤-23	80km	Duplex LC	C/I
XFP BIDI	XFP-BL23TG-10Dx	10.3Gb/s	1270T/1330R	-5 ~ 0	≤-12.5	10km	Single LC	C/I
	XFP-BL32TG-10Dx	10.3Gb/s	1330T/1270R	-5 ~ 0	≤-12.5	10km	Single LC	C/I
	XFP-BL23TG-20Dx	10.3Gb/s	1270T/1330R	-3.0 ~ +2.0	≤-14.5	20km	Single LC	C/I
	XFP-BL32TG-20Dx	10.3Gb/s	1330T/1270R	-3.0 ~ +2.0	≤-14.5	20km	Single LC	C/I
	XFP-BL23TG-40Dx	10.3Gb/s	1270T/1330R	-1 ~ +5	≤-15	40km	Single LC	C/I
	XFP-BL32TG-40Dx	10.3Gb/s	1330T/1270R	-1 ~ +5	≤-15	40km	Single LC	C/I
	XFP-BL23TG-60Dx	10.3Gb/s	1270T/1330R	+1 ~ +6	≤-20	60km	Single LC	C/I
	XFP-BL32TG-60Dx	10.3Gb/s	1330T/1270R	+1 ~ +6	≤-20	60km	Single LC	C/I
	XFP-BL45TG-80Dx	10.3Gb/s	1490T/1550R	0 ~ +4	≤-23	80km	Single LC	C/I
	XFP-BL54TG-80Dx	10.3Gb/s	1550T/1490R	0 ~ +4	≤-23	80km	Single LC	C/I

Operating case temperature:C= 0 to +70°C I= -40 to +85°C