





产品目录

PRODUCT CATALOG

155M-3.1G SFP

|  TOPLINK | Part Number | Data Rate | Wavelength(nm) | Tx Power(dBm) | Rx Sen(dBm) | Reach | Connector | Temp. |
|--|-----------------|-----------|----------------|---------------|-------------|-------|-----------|-------|
| SFP 155M | SFP-MM8503-02Dx | 155Mb/s | 850 | -10 ~ +2 | ≤-23 | 2km | Duplex LC | C/I |
| | SFP-MM3103-02Dx | 155Mb/s | 1310 | -18 ~ -10 | ≤-26 | 2km | Duplex LC | C/I |
| | SFP-SM3103-20Dx | 155Mb/s | 1310 | -14 ~ -8 | ≤-32 | 20km | Duplex LC | C/I |
| | SFP-SM3103-40Dx | 155Mb/s | 1310 | -8 ~ -3 | ≤-32 | 40km | Duplex LC | C/I |
| | SFP-SM5503-40Dx | 155Mb/s | 1550 | -8 ~ -3 | ≤-32 | 40km | Duplex LC | C/I |
| | SFP-SM5503-80Dx | 155Mb/s | 1550 | -5 ~ +2 | ≤-32 | 80km | Duplex LC | C/I |
| | SFP-SM5503-A2Dx | 155Mb/s | 1550 | 0 ~ +5 | ≤-34 | 120km | Duplex LC | C/I |
| SFP 622M | SFP-MM8512-02Dx | 622Mb/s | 850 | -9 ~ 0 | ≤-18 | 550m | Duplex LC | C/I |
| | SFP-SM3112-20Dx | 622Mb/s | 1310 | -15 ~ -8 | ≤-28 | 20km | Duplex LC | C/I |
| | SFP-SM3112-40Dx | 622Mb/s | 1310 | -8 ~ -3 | ≤-28 | 40km | Duplex LC | C/I |
| | SFP-SM5512-40Dx | 622Mb/s | 1550 | -8 ~ 0 | ≤-28 | 40km | Duplex LC | C/I |
| | SFP-SM5512-80Dx | 622Mb/s | 1550 | -3 ~ +3 | ≤-28 | 80km | Duplex LC | C/I |
| | SFP-SM5512-A2Dx | 622Mb/s | 1550 | 1 ~ 5 | ≤-29 | 120km | Double LC | C/I |
| SFP 1.25G | SFP-MM8524-S5Dx | 1.25Gb/s | 850 | -9 ~ 0 | ≤-18 | 550m | Duplex LC | C/I |
| | SFP-MM3124-02Dx | 1.25Gb/s | 1310 | -13 ~ -3 | ≤-21 | 2km | Duplex LC | C/I |
| | SFP-SM3124-20Dx | 1.25Gb/s | 1310 | -9 ~ 0 | ≤-23 | 20km | Duplex LC | C/I |
| | SFP-SM3124-40Dx | 1.25Gb/s | 1310 | -5 ~ 0 | ≤-23 | 40km | Duplex LC | C/I |
| | SFP-SM5524-40Dx | 1.25Gb/s | 1550 | -5 ~ 0 | ≤-23 | 40km | Duplex LC | C/I |
| | SFP-SM5524-80Dx | 1.25Gb/s | 1550 | 0 ~ +5 | ≤-26 | 80km | Duplex LC | C/I |
| | SFP-SM5524-A2Dx | 1.25Gb/s | 1550 | 1 ~ 5 | ≤-28 | 120km | Duplex LC | C/I |
| SFP 2.5G | SFP-MM8548-S3Dx | 2.5Gb/s | 850 | -9 ~ 0 | ≤-18 | 330m | Duplex LC | C/I |
| | SFP-SM3148-02Dx | 2.5Gb/s | 1310 | -10 ~ -3 | ≤-18 | 2km | Duplex LC | C/I |
| | SFP-SM3148-10Dx | 2.5Gb/s | 1310 | -9 ~ -3 | ≤-18 | 10km | Duplex LC | C/I |
| | SFP-SM3148-20Dx | 2.5Gb/s | 1310 | -6 ~ +1 | ≤-18 | 20km | Duplex LC | C/I |
| | SFP-SM5548-20Dx | 2.5Gb/s | 1550 | -6 ~ +1 | ≤-18 | 20km | Duplex LC | C/I |
| | SFP-SM3148-40Dx | 2.5Gb/s | 1310 | -2 ~ +3 | ≤-20 | 40km | Duplex LC | C/I |
| | SFP-SM5548-40Dx | 2.5Gb/s | 1550 | -2 ~ +3 | ≤-20 | 40km | Duplex LC | C/I |
| | SFP-SM5548-80Dx | 2.5Gb/s | 1550 | 0 ~ +5 | ≤-26 | 80km | Duplex LC | C/I |

|  | | | | | | | | |
|--|-----------------|----------|--------------------|----------|------|-------|-----------|-----|
| SFP CWDM | SFP-CWxx03-40Dx | 155Mb/s | 1270 ~ 1610 | -5 ~ 0 | ≤-32 | 40km | Duplex LC | C/I |
| | SFP-CWxx03-80Dx | 155Mb/s | 1270 ~ 1610 | -3 ~ +2 | ≤-32 | 80km | Duplex LC | C/I |
| | SFP-CWxx03-A2Dx | 155Mb/s | 1470 ~ 1610 | 0 ~ +5 | ≤-34 | 120km | Duplex LC | C I |
| | SFP-CWxx24-40Dx | 1.25Gb/s | 1270 ~ 1610 | -5 ~ 0 | ≤-24 | 40km | Double LC | C/I |
| | SFP-CWxx24-60Dx | 1.25Gb/s | 1270 ~ 1610 | -1 ~ +3 | ≤-24 | 60km | Double LC | C/I |
| | SFP-CWxx24-80Dx | 1.25Gb/s | 1270 ~ 1610 | 0 ~ +4 | ≤-26 | 80km | Double LC | C/I |
| | SFP-CWxx24-A2Dx | 1.25Gb/s | 1470 ~ 1610 | 0 ~ +5 | ≤-28 | 120km | Double LC | C/I |
| | SFP-CWxx48-40Dx | 2.5Gb/s | 1270 ~ 1610 | -2 ~ +3 | ≤-19 | 40km | Double LC | C/I |
| | SFP-CWxx48-80Dx | 2.5Gb/s | 1270 ~ 1610 | 0 ~ +5 | ≤-26 | 80km | Double LC | C/I |
| SFP DWDM | SFP-DWxx24-40Dx | 1.25Gb/s | ITU-T G.692 C21-61 | -3 ~ +2 | ≤-24 | 40km | Double LC | C/I |
| | SFP-DWxx24-80Dx | 1.25Gb/s | ITU-T G.692 C21-61 | 0 ~ +4 | ≤-30 | 80km | Double LC | C/I |
| | SFP-DWxx24-A2Dx | 1.25Gb/s | ITU-T G.692 C21-61 | 0 ~ +4 | ≤-32 | 120km | Double LC | C/I |
| | SFP-DWxx48-40Dx | 2.5Gb/s | ITU-T G.692 C21-61 | -3 ~ +2 | ≤-20 | 40km | Double LC | C/I |
| | SFP-DWxx48-80Dx | 2.5Gb/s | ITU-T G.692 C21-61 | 0 ~ +4 | ≤-28 | 80km | Double LC | C/I |
| | SFP-DWxx48-A2Dx | 2.5Gb/s | ITU-T G.692 C21-61 | 0 ~ +4 | ≤-30 | 120km | Double LC | C/I |
| SFP BIDI | SFP-BL3503-03Dx | 155Mb/s | 1310/1550 | -14 ~ -8 | ≤-23 | 3km | Single LC | C/I |
| | SFP-BL5303-03Dx | 155Mb/s | 1550/1310 | -14 ~ -8 | ≤-23 | 3km | Single LC | C/I |
| | SFP-BL3503-20Dx | 155Mb/s | 1310/1550 | -14 ~ -8 | ≤-32 | 20km | Single LC | C/I |
| | SFP-BL5303-20Dx | 155Mb/s | 1550/1310 | -14 ~ -8 | ≤-32 | 20km | Single LC | C/I |
| | SFP-BL3503-40Dx | 155Mb/s | 1310/1550 | -8 ~ -2 | ≤-32 | 40km | Single LC | C/I |
| | SFP-BL5303-40Dx | 155Mb/s | 1550/1310 | -8 ~ -2 | ≤-32 | 40km | Single LC | C/I |
| | SFP-BL4503-80Dx | 155Mb/s | 1490/1550 | -5 ~ +2 | ≤-32 | 80km | Single LC | C/I |
| | SFP-BL5403-80Dx | 155Mb/s | 1550/1490 | -5 ~ +2 | ≤-32 | 80km | Single LC | C/I |

| SFP BIDI | SFP BIDI | | SFP BIDI | | SFP BIDI | | SFP BIDI | |
|----------|-----------------|----------|------------|-------------|----------|-----------|--------------|-----|
| | Model | Speed | Wavelength | Temperature | Distance | Port Type | Compliance | |
| | SFP-Bx3524-03Dx | 1.25Gb/s | 1310/1550 | -14 ~ -8 | ≤-23 | 3km | Single LC/SC | C/I |
| | SFP-Bx5324-03Dx | 1.25Gb/s | 1550/1310 | -14 ~ -8 | ≤-23 | 3km | Single LC/SC | C/I |
| | SFP-Bx3524-20Dx | 1.25Gb/s | 1310/1550 | -9 ~ 0 | ≤-23 | 20km | Single LC/SC | C/I |
| | SFP-Bx5324-20Dx | 1.25Gb/s | 1550/1310 | -9 ~ 0 | ≤-23 | 20km | Single LC/SC | C/I |
| | SFP-Bx3524-40Dx | 1.25Gb/s | 1310/1550 | -5 ~ 0 | ≤-24 | 40km | Single LC/SC | C/I |
| | SFP-Bx5324-40Dx | 1.25Gb/s | 1550/1310 | -5 ~ 0 | ≤-24 | 40km | Single LC/SC | C/I |
| | SFP-Bx3424-20Dx | 1.25Gb/s | 1310/1490 | -9 ~ 0 | ≤-23 | 20km | Single LC/SC | C/I |
| | SFP-Bx4324-20Dx | 1.25Gb/s | 1490/1310 | -9 ~ 0 | ≤-23 | 20km | Single LC/SC | C/I |
| | SFP-Bx3424-40Dx | 1.25Gb/s | 1310/1490 | -5 ~ 0 | ≤-23 | 40km | Single LC/SC | C/I |
| | SFP-Bx4324-40Dx | 1.25Gb/s | 1490/1310 | -5 ~ 0 | ≤-23 | 40km | Single LC/SC | C/I |
| | SFP-Bx4524-80Dx | 1.25Gb/s | 1490/1550 | 0 ~ +5 | ≤-26 | 80km | Single LC/SC | C/I |
| | SFP-Bx5424-80Dx | 1.25Gb/s | 1550/1490 | 0 ~ +5 | ≤-26 | 80km | Single LC/SC | C/I |
| | SFP-Bx4524-A0Dx | 1.25Gb/s | 1490/1550 | 0 ~ +5 | ≤-28 | 100km | Single LC/SC | C/I |
| | SFP-Bx5424-A0Dx | 1.25Gb/s | 1550/1490 | 0 ~ +5 | ≤-28 | 100km | Single LC/SC | C/I |
| | SFP-Bx4524-A2Dx | 1.25Gb/s | 1490/1550 | 1 ~ +5 | ≤-28 | 120km | Single LC/SC | C/I |
| | SFP-Bx5424-A2Dx | 1.25Gb/s | 1550/1490 | 1 ~ +5 | ≤-28 | 120km | Single LC/SC | C/I |
| | SFP-BL3548-10Dx | 2.5Gb/s | 1310/1550 | -8 ~ -3 | ≤-18 | 10km | Single LC | C/I |
| | SFP-BL5348-10Dx | 2.5Gb/s | 1550/1310 | -8 ~ -3 | ≤-18 | 10km | Single LC | C/I |
| | SFP-BL3548-20Dx | 2.5Gb/s | 1310/1550 | -5 ~ 0 | ≤-18 | 20km | Single LC | C/I |
| | SFP-BL5348-20Dx | 2.5Gb/s | 1550/1310 | -5 ~ 0 | ≤-18 | 20km | Single LC | C/I |
| | SFP-BL3548-40Dx | 2.5Gb/s | 1310/1550 | -2 ~ +4 | ≤-20 | 40km | Single LC | C/I |
| | SFP-BL5348-40Dx | 2.5Gb/s | 1550/1310 | -2 ~ +4 | ≤-20 | 40km | Single LC | C/I |
| | SFP-BL4548-80Dx | 2.5Gb/s | 1490/1550 | 0 ~ +5 | ≤-26 | 80km | Single LC | C/I |
| | SFP-BL5448-80Dx | 2.5Gb/s | 1550/1490 | 0 ~ +5 | ≤-26 | 80km | Single LC | C/I |

Operating case temperature:C= 0 to +70°C I= -40 to +85°C